

**SKARE
PROFESIONALE**



SPECIFIKAT TEKNIKE

| | NFT78GL | NFT76GTMC |
|--------------------------|----------------|-------------------------------------|
| Fuqia termike | 2 x 6 kW | 11 kW |
| Sirtari për pastrim | 2.5 litra | 2.5 litra |
| Kontrolli i temperaturës | manual | termostat |
| Temperatura | 200 - 400°C | 110 - 280°C |
| Pllaka punuese | inox 304 | krom (2/3 e rrafshët - 1/3 me vija) |
| Dim i hapsirës punuese | 73.5x53cm | 53.5x53cm |
| Dim i skarës | 80x73x25h/cm | 60x73x25h/cm |

**SKARE
PROFESIONALE**



SPECIFIKAT TEKNIKE

| | NFT78GTLC | SDFT12GTLC |
|--------------------------|------------------|-------------------|
| Fuqia termike | 2 x 7 kW | 3 x 10.5 kW |
| Sirtari për pastrim | 2.5 litra | 2 x 3 litra |
| Kontrolli i temperaturës | termostat | termostat |
| Temperatura | 110 - 280°C | 110 - 280°C |
| Pllaka punuese | krom | krom |
| Dim i hapsirës punuese | 73.5x53cm | 112x70cm |
| Dim i skarës | 80x73x25h/cm | 120x92x28h/cm |



**SHPORET DHE
KIPER PROFESIONAL**

NC78G24

NRB78GI
SPECIFIKAT TEKNIKE

| | NC78G24 | NRB78GI |
|--------------------------|----------------|----------------|
| Fuqia termike | 4 x 6 kW | 2 x 14 kW |
| Kapaciteti | 4 X 40x29cm | 60 litra |
| Kontrolli i temperaturës | manual | termostat |
| Temperatura | - | 100 - 280°C |
| Dim i hapsirës punuese | 4 X 40x29cm | 77x54x20h/cm |
| Dim i pajisjës | 80x73x23h/cm | 80x73x90h/cm |

**FRITEZE DHE
PAJISJE PER PASTA**

NF76G8

NPC74G
SPECIFIKAT TEKNIKE

| | NF76G8 | NPC74G |
|--------------------------|------------------|---------------|
| Fuqia termike | 2 x 7 kW | 10.5 kW |
| Kapaciteti | 2 X 8 litra | 28 litra |
| Kontrolli i temperaturës | termostat | termostat |
| Temperatura | 100 - 185°C | 110 - 280°C |
| Dim i hapsirës punuese | 2 X 20x34x11h/cm | 31x34x27cm |
| Dim i pajisjës | 60x73x25h/cm | 40x73x90h/cm |



*FURRE ELEKTRIKE
KONVENCIONALE*



SPECIFIKAT TEKNIKE

| | XF-023 | XFT-135 |
|----------------------|---------------|----------------|
| Fuqia termike | 3 kW | 3 kW |
| Kapaciteti | 4 X 46x33cm | 4 X 46x33cm |
| Hapësira e rendeve | 7 cm | 7.5 cm |
| Temperatura | 30 - 260°C | 30 - 260°C |
| Kontrolli | manual | dijital |
| Furnizimi me energji | 230V | 230V |
| Dimensioni | 60x47x59h/cm | 60x65x51h/cm |

*Mundesi te programimit deri ne 99
receptura, secila ne 3 hapa per pjekje
plus parapregaditja.*

*FURRE ELEKTRIKE
KONVENCIONALE*



SPECIFIKAT TEKNIKE

| | XV-393 | XB-693 |
|----------------------|---------------|---------------|
| Fuqia termike | 7.1 kW | 10.3 kW |
| Kapaciteti | 5 X 53x32.5cm | 6 X 60x40cm |
| Hapësira e rendeve | 6.7 cm | 8 cm |
| Temperatura | 30 - 260°C | 30 - 260°C |
| Kontrolli | manual | manual |
| Furnizimi me energji | 400V | 400V |
| Dimensioni | 75x77x77h/cm | 86x88x93h/cm |

Për ndryshime në specifika kontakto me shitësin.



FURRE ELEKTRIKE
KONVENCIONALE



SPECIFIKAT TEKNIKE

XFT-185

XEBC-04EU-EPR

Fuqia termike

3.3 kW

10.6 kW

Kapaciteti

3 X 60x40cm

4 X 60x40cm

Hapësira e rendeve

7.5 cm

8 cm

Temperatura

30 - 260°C

30 - 260°C

Kontrolli

dijital

dijital

Furnizimi me energji

230V

400V

Dimensioni

80x77x43h/cm

86x96x67.5h/cm

*Mundesi te programimit deri ne 99
receptura, secila ne 3 hapa per pjekje
plus parapregaditja.*

*Mundesi te programimit deri ne 256
receptura, secila ne hapa pa limit per
pjekje dhe parapregaditja. Larje auto-
matike.*

FURRE ELEKTRIKE
KONVENCIONALE



SPECIFIKAT TEKNIKE

XB-695

XEVC-2011-EPR

Fuqia termike

10.5 kW

35 kW

Kapaciteti

6 X 60x40cm

20 X 53x32.5cm

Hapësira e rendeve

8 cm

7 cm

Temperatura

30 - 260°C

30 - 260°C

Kontrolli

dijital

dijital

Furnizimi me energji

400V

400V

Dimensioni

86x88x93h/cm

88x105x187h/cm

*Mundesi te programimit deri ne 99
receptura, secila ne 3 hapa per pjekje
plus parapregaditja.*

*Mundesi te programimit deri ne 256
receptura, secila ne hapa pa limit per
pjekje dhe parapregaditja. Larje auto-
matike.*



SPECIFIKAT TEKNIKE

| | ALFA 4 | ALFA 44 |
|----------------------|--------------------|--------------------|
| Temperatura | 50 - 500°C | 50 - 500°C |
| Furnizimi me energji | 400V | 400V |
| Fuqia elektrike | 4.7 kW | 9.4 kW |
| Kapaciteti | 4 pica Ø32 | 8 pica Ø32 |
| Dim i mbrendshëm | 66x66x14h/cm | 2 X 66x66x14h/cm |
| Dim i jashtëm | 97.5x92.5x41.3h/cm | 97.5x92.5x74.5h/cm |



SPECIFIKAT TEKNIKE

| | ALFA XL4 | ALFA XL44 |
|----------------------|-------------------|-------------------|
| Temperatura | 50 - 500°C | 50 - 500°C |
| Furnizimi me energji | 400V | 400V |
| Fuqia elektrike | 6 kW | 12 kW |
| Kapaciteti | 4 pica Ø35 | 8 pica Ø35 |
| Dim i mbrendshëm | 72x72x14h/cm | 2 X 72x72x14h/cm |
| Dim i jashtëm | 100x95.5x41.3h/cm | 100x95.5x74.5h/cm |



SPECIFIKAT TEKNIKE

| | ALFA 6 | ALFA 66 |
|----------------------|---------------------|---------------------|
| Temperatura | 50 - 500°C | 50 - 500°C |
| Furnizimi me energji | 400V | 400V |
| Fuqia elektrike | 7.2 kW | 14.4 kW |
| Kapaciteti | 6 pica Ø32 | 12 pica Ø32 |
| Dim i mbrendshëm | 66x99x14h/cm | 2 X 66x99x14h/cm |
| Dim i jashtëm | 97.5x121.5x41.3h/cm | 97.5x121.5x74.5h/cm |

Optimade

FURRE PER PICA



SPECIFIKAT TEKNIKE

ALFA XL6

ALFA XL66

| | | |
|----------------------|--------------------|-------------------|
| Temperatura | 50 - 500°C | 50 - 500°C |
| Furnizimi me energji | 400V | 400V |
| Fuqia elektrike | 9 kW | 18 kW |
| Kapaciteti | 6 pica Ø35 | 12 pica Ø35 |
| Dim i mbrendshëm | 72x108x14h/cm | 2 X 72x108x14h/cm |
| Dim i jashtëm | 100x131.5x41.3h/cm | 100x131x74.5h/cm |

FURRE PER PICA



SPECIFIKAT TEKNIKE

ALFA XL9

ALFA XL99

| | | |
|----------------------|--------------------|--------------------|
| Temperatura | 50 - 500°C | 50 - 500°C |
| Furnizimi me energji | 400V | 400V |
| Fuqia elektrike | 13.2 kW | 26.4 kW |
| Kapaciteti | 9 pica Ø35 | 18 pica Ø35 |
| Dim i mbrendshëm | 108x108x14h/cm | 2 X 108x108x14h/cm |
| Dim i jashtëm | 136x131.5x41.3h/cm | 136x131.5x74.5h/cm |

FURRE PER PICA



SPECIFIKAT TEKNIKE

MIZAR 4

MIZAR 44

| | | |
|----------------------|---------------------------|---------------------------|
| Temperatura | 50 - 500°C | 50 - 500°C |
| Furnizimi me energji | 400V | 400V |
| Fuqia elektrike | 6.9 kW | 13.8 kW |
| Kapaciteti | (4 X Ø40) - (2 X 60x40cm) | (8 X Ø40) - (4 X 60x40cm) |
| Dim i mbrendshëm | 82x84x17.5h/cm | 2 X 82x84x17.5h/cm |
| Dim i jashtëm | 110x107.5x41.3h/cm | 110x107.5x74.5h/cm |

FURRE PER PICA



SPECIFIKAT TEKNIKE

MAXINE 1/40

MAXINE 1/50

| | | |
|----------------------|--------------|------------------|
| Temperatura | 50 - 320°C | 50 - 500°C |
| Furnizimi me energji | 230V | 400V |
| Fuqia elektrike | 1.6 kW | 5 kW |
| Dim i mbrendshëm | 41X36X9h/cm | 62X50X12h/cm |
| Dim i jashtëm | 57X50X28h/cm | 91.5X69X35.7h/cm |

HOLLES I BRUMIT TE PICAVE



SPECIFIKAT TEKNIKE

SIGMA 420

SIGMA 420TGO

| | | |
|----------------------|----------------|----------------|
| Kapaciteti | 200g - 700g | 200g - 700g |
| Diametri i holluesit | 26cm - 40cm | 26cm - 40cm |
| Furnizimi me energji | 230V | 230V |
| Komanda | manuale | dijjtale |
| Dimensioni | 58x46.5x78h/cm | 58x46.5x78h/cm |